

TRENCH IT - TCT AG TRENCHER



Features and Information

This is a PTO driven trencher. Driven via a reduction gearbox and chain drive. It comes with a driveshaft and slip clutch to protect tractor and trencher from undue shock loading.

It is designed for tractors with horsepower (HP) from 40 – 70HP with hydrostatic transmission or creep gearbox that does not exceed 0.2 kph or 0.12 miles/hr.

This is a heavy duty trencher, and runs a 2" Pitch trenching chain.

This can be used with a conveyor or without. The conveyor is an extra accessory.

The tractor should be fitted with rear auxiliary hydraulics, this is for the operation of the hydraulic ram for depth control.

Note:
Front counter weights or loader may be necessary for proper transportation and operation of the tractor trencher.

Digging Depth: Up to 1200mm with various chain options.

Digging Width: From 150 – 300mm wide trench with various chain options.

Wear Parts: Quality USA trenching parts, with tungsten carbide cutting teeth.

Slip Clutch: This protects tractor and trencher from undue shock loading.

Spoil Handling: Auger places soil neatly to one side, to allow easy access to trench.

Crumber Bar: Grades trench as you go.

TRENCHIT
INDUSTRIES LTD

Phone: 07 578 1612 Fax: 07 571 8808
Freephone: 0800 873 624 Email: trenchitz@xtra.co.nz
5/67 Courtney Road, Tauranga PO Box 16098, Tauranga
New Zealand www.trenchit.co.nz