

TRENCH-IT TMT - JD4310



FOR STRENGTH, LOW MAINTENANCE, RELIABILITY & PERFORMANCE

PRIME MOVER

John Deere 4310 HST 4 Wheel drive tractor

ENGINE

John Deere water cooled 3-cylinder diesel 32 HP.

FUEL CAPACITY

37.9 Litres

HYDRAULICS SYSTEM

Flow 52.5 lts/min, pressure 2,500 p.s.i
Quadruple bank with twin controls for blade
Single control for boom raise & lower

BACKFILL BLADE

Fully hydraulic – raises and lowers, tilts left and right, angles at 30° maximum left or right

WEIGHT

2,400 KG

DIMENSIONS

Length	4.758 metres
Width	1.54 metres
Height	2.127 metres
Clearance	1.9 metres

DIGGING CHAIN

2 inch pitch 50,000kg test

TRENCH

Centre mounted	100-300mm wide
Side mounted	100-200mm wide
Standard width	150mm
Standard depth	1 metre

INFORMATION CONTACT

	<p>Phone: 07 578 1612 Fax: 07 571 8808 Freephone: 0800 873 624 Email: trenchitnz@xtra.co.nz 5/67 Courtney Road, Tauranga PO Box 16098, Tauranga New Zealand www.trenchit.co.nz</p>
---	---